

LED line LITE

Code: 211605-II

EAN: 5905378220096

Hermetic luminaire LINIX 4000K 36W 4320lm IP65 120cm gray LITE



LINIX LITE is a modern LED fixture with high energy efficiency and durability. With a luminous efficiency of 120 lm/W and a wide beam angle of 120°, it provides even and comfortable lighting.

The fixtures can be connected in continuous light lines, allowing for flexible adaptation of lighting to large spaces. With easy installation and a solid construction, LINIX LITE is an excellent choice for demanding users.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 36 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IEC protection class	II
Luminous efficacy	120
Luminous flux	4320
Lifetime L70B50	20 000 h
Colour consistency in McAdam ellipses	≤6
Mounting type	mixed

Parameter	Value
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
Lifespan	20 000 h
Power Factor	0,95
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Length	1237
Width	53
Height	35
Weight	0,33 kg
Material (housing)	Polycarbonate
Material (cover)	Polystyrene

LED line LITE


Code: 211605-II

EAN: 5905378220096


Hermetic luminaire LINIX 4000K 36W

4320lm IP65 120cm gray LITE

Technical drawing




Light distribution



Additional product photos




Logistics data




Single packaging

Quantity	
Width	51 mm
Height	25 mm
Length	1275 mm
Weight	0,33 kg



Bulk packaging

Quantity	30
Width	275 mm
Height	230 mm
Length	1280 mm
Weight	9,9 kg



Europallet

Quantity	360
Height	1900 mm
Quantity in layer	12
Number of layers	1
Bulk quantity	12
Weight	140 kg

LED line LITE

Code: 211605-II

EAN: 5905378220096

**Hermetic luminaire LINIX 4000K 36W
4320lm IP65 120cm gray LITE**

Example application

