

LED line PRIME

Code: 201057-AW3HAT

EAN: 5905378212206

LINKER TRI-PROOF 80W 4000K  
12000lm 150lm/W 220-240V IP65 150cm  
Emergency module 3H AT PRIME



Linker 80W from LED line PRIME is a modern and efficient light source, offering a brightness of 12000 lumens, which provides excellent lighting in all conditions. Light performance of 150 lm/W and colour temperature 4000 K guarantee natural color reproduction. IP65 leak class provides resistance to water and dust, and emergency mode time up to 3 hours increases safety.



Technical data

| Parameter                             | Value          |
|---------------------------------------|----------------|
| Energy efficiency class 2019/2015     | D              |
| Warranty                              | 5              |
| Power                                 | • 80 W         |
| Voltage                               | • 220-240 V AC |
| Correlated colour temperature         | • 4000 K       |
| Colour of the light                   | White          |
| Colour rendering index Ra             | 80             |
| IP protection rating                  | IP65           |
| IK protection rating                  | 08             |
| IEC protection class                  | II             |
| Luminous efficacy                     | 150            |
| Luminous flux                         | 12000          |
| The lumen maintenance factor          | 96             |
| Lifetime L70B50                       | 100 000 h      |
| Survival factor                       | 0.9            |
| Dimmable function                     | PWM            |
| Colour consistency in McAdam ellipses | ≤6             |
| ULOR                                  | 3%             |

| Parameter                                  | Value         |
|--------------------------------------------|---------------|
| Emergency module test                      | Autotest      |
| Operating time in emergency mode           | 3 h           |
| Frequency of the supply voltage            | 50/60Hz       |
| Beam angle                                 | 120           |
| Lifespan                                   | 100 000 h     |
| Power Factor                               | 0,95          |
| Number of on/off cycles                    | 50000         |
| Lamp's warm-up time to 60%                 | 1             |
| Ambient temperature suitable for operation | -25 ÷ 45      |
| Length                                     | 1500 mm       |
| Width                                      | 72 mm         |
| Height                                     | 61 mm         |
| Weight                                     | 1,76 kg       |
| Colour                                     | Grey          |
| Material (housing)                         | Polycarbonate |
| Material (cover)                           | Polycarbonate |
| Emergency module                           | • YES         |

LED line PRIME


Code: 201057-AW3HAT

EAN: 5905378212206

LINKER TRI-PROOF 80W 4000K  
12000lm 150lm/W 220-240V IP65 150cm  
Emergency module 3H AT PRIME

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

|          |         |
|----------|---------|
| Quantity | 1       |
| Width    | 75 mm   |
| Height   | 65 mm   |
| Length   | 1570 mm |
| Weight   | 1,95 kg |

Bulk packaging

|          |          |
|----------|----------|
| Quantity | 12       |
| Width    | 288 mm   |
| Height   | 246 mm   |
| Length   | 1538 mm  |
| Volume   | 0,102 m3 |
| Weight   | 28,2 kg  |

Europallet

|                   |         |
|-------------------|---------|
| Quantity          | 144     |
| Height            | 1750 mm |
| Quantity in layer |         |
| Number of layers  |         |
| Bulk quantity     | 12      |
| Weight            | 363 kg  |

---

LED line PRIME

Code: 201057-AW3HAT

EAN: 5905378212206

**LINKER TRI-PROOF 80W 4000K  
12000lm 150lm/W 220-240V IP65 150cm  
Emergency module 3H AT PRIME**

---

Example application